



**MEOR**

*Maximizing Earths Original Resources, L.L.C.*

4610 S. 33<sup>rd</sup> Place • Phoenix, AZ 85040 • Phone: (480) 929-9194 • Fax: (480) 219-6875 • www.meor.net

## **TECHNICAL DATA SHEET**

### **SLUDGE SLAMMER™**

Sludge Slammer™ is a concentrated reliquification product created to utilize the most innovative chemistries available in reducing oil viscosity and increasing API specific gravity to increase flow rates of oil and oil by products. Sludge Slammer™ is also an excellent product for removing sludge from tanks, sludge pits, oil rigs and refinery equipment as well as reducing asphaltene and paraffin buildup on the sides of oil transfer lines to return piping back to its original size.

Sludge Slammer™ is advanced state of the art reliquification product composed of homogeneous substances designed to re-mediate petroleum based compounds. These compounds include oil and grease, distillate fuel oils, residual oils, lubricants, and other products resulting from the straight distillation of crude oil, distillation of unfinished petroleum derivatives, cracking and other petroleum processes.

#### **How it works**

Sludge Slammer™ reliquifies the HC chain on contact reducing the heavy oils and paraffin's to a more easily transferable state. This reduction aids in the removal of sludge in storage tanks, paraffin in oil transfer lines, improves the quality of crude oils, reduces oil viscosity and increases API specific gravity as well as greatly improves the velocity of oil transfer through the transfer lines with a corresponding reduction in oil pumping costs. The oil is not harmed and is saleable which greatly increases profit margins and reduces oil production costs.

#### **Application**

Sludge Slammer™ is used for heavy industrial applications. It has 100% active ingredients and contains no water, use full-strength, do not dilute. Check for compatibility prior to use. The typical percentage for tank cleaning is about 1% of sludge volume.

This product can be poured, sprayed or wiped on problem area. Allow sufficient time for product to penetrate (penetration time will vary with different applications); Wipe off or rinse with mild soap and clean water for residue free surfaces.

#### **Packaging**

Sludge Slammer™ is packaged in 5 and 55-gallon poly containers and totes.